



Front grille with screw fixing



Stainless steel ground, grain 240



Tested to VDI 6022

Fluff separator Type FSG



For separating fluff and textile fibres in operating rooms and adjoining operating rooms

Use in health care buildings and rooms

- Completely made of stainless steel
- Grille face can be dismantled without tools
- Grinded grille face frame, grain size 240
- Easy cleaning
- Disinfectant-resistant
- Stainless steel wire mesh with narrow mesh width (0.5 mm)
- According to the requirements of DIN 1946 Part 4
- Meets the hygiene requirements of VDI 6022





General information2Dimensions5Specification text3Product details6Order code4

General information

Application

- For wall mounting in health care rooms
- Wire cloth for separating fluff and textile fibres from surgical clothing or surgical drapes

Classification

- Hygiene-conformity according to VDI 6022
- Construction according to DIN 1946 Part 4

Nominal sizes

- BxH
- Width 225 mm to 625 mm
- Height 225 mm to 425 mm

Special characteristics

- Compact construction
- Easy cleaning
- Sizes available in 1 mm increments
- Tool-free, simple assembly and disassembly of the grille face frame with knurled screws
- Stainless steel wire mesh

Construction features

- Frame welded and pickled
- Wire cloth according to ISO 9044
- Mesh aperture 0.5 mm
- wire diameter 0.315 mm

Materials and surfaces

- Material stainless steel (1.4301)
- Grinded grille face frame, grain size 240

Installation and commissioning

- · Grille face frame with wire mesh
- Grille face frame with screw fixing
- Connection to air duct provided by customer

Standards and guidelines

 Hygiene meets the requirements of VDI 6022, VDI 3803, DIN 1946 Part 4, ÖNORM H 6021 and ÖNORM H 6020, SWKI VA 104-01 and SWKI 99-3, and EN 16798

Maintenance

2

Easy disassembly of grille face frame for cleaning and decontamination





Specification text

This specification text describes the general properties of the product. Texts for variants can be generated with our Easy

Product Finder design programme.

Specification text

FSG fluff separator for separating fluff and textile fibres from surgical clothing and surgical drapes in health care rooms. The separation of the fluff takes place directly on the surface of the wire cloth at the suction point. The air ducts and the downstream filters are effectively protected against fibrous particles. The economical and trouble-free operation of the air conditioning systems is ensured. The fluff separator can be easily cleaned using conventional methods. For this purpose, the knurled screws are loosened from the grille face frame. The frame is then removed from the holder. After cleaning, reassembly is carried out in reverse order.

Special characteristics

- Compact construction
- Easy cleaning
- Sizes available in 1 mm increments
- Toolless fastening of the grille face frame with wire mesh
- Simple assembly and disassembly due to bolted grille face frame
- Stainless steel wire mesh

Materials and surfaces

- Material stainless steel 1.4301
- Front polished, grain 240
- Special version material stainless steel (1.4571) on request





Order code

1 Type

FSG Fluff separator

2 Construction

Construction

S Grille face with screw fixing

Nominal size

Order example: FSG-S/425x225

425 x 225 mm

225 ≤ B ≤ 625

225 ≤ H ≤ 425

B x H


Grille face with screw fixing

3 Nominal size [mm]





Dimensions



Product specific data

- 3												
	В	B 225		325		425		525		625		
	Н	kg	m³/h	kg	m³/h	kg	m³/h	kg	m³/h	kg	m³/h	
	225	1,4	190	1,7	320	2,1	450	2,6	580	3	710	
	325	1,7	320	2,2	540	2,6	760	3,1	980	3,5	1200	
	425	2,1	450	2,6	760	3,1	1070	3,3	1380	4,1	1690	

5

Sizes in the nominal dimension range available in 1 mm increments. Sizes according to the table are standard on the market.





Product details

Stainless steel ground grain 240



Knurled screw for tool-free fastening



Screwed construction



Front grille frame with wire mesh



