



POCKET FILTER, TYPE  
PFG



TESTED TO  
VDI 6022

Conforms to VDI 6022



Eurovent certification



ATEX-ZERTIFIZIERUNG

ATEX construction optional

## PFG



### PREFILTERS OR FINAL FILTERS IN VENTILATION SYSTEMS

Pocket filters for the separation of fine dust

- Filter groups ISO ePM10 and ISO ePM1 (fine dust filters)
- Performance tested to ISO 16890
- Eurovent certification for fine dust filters
- Meets the hygiene requirements of VDI 6022
- High energy efficiency class according to Eurovent
- Non-woven glass fibres, sewn
- Enlarged filter area due to filter pockets
- Low initial differential pressure and high dust holding capacity, ideal airflow conditions due to wedge-shaped filter pockets
- Different numbers of pockets and pocket depths
- Quick installation and filter changing times due to easy, safe handling
- Fitting into standard cell frames for filter walls (type SIF) or into universal casings (type UCA) for duct installation

Optional equipment and accessories

- Front frame made of plastic or galvanised sheet steel
- ATEX construction for protection zones 1 and 2 as well as 21 and 22

## General information

---



### Application

- Pocket filter made of non-woven glass fibres type PFG for the separation of fine dust
- Fine dust filter: Prefilter or final filter in ventilation systems

### Classification

- Eurovent certification for fine dust filters
- Meets the hygiene requirements
- Certificate of conformity for use in areas with a potentially explosive atmosphere

### Nominal sizes

- B × H × D [mm]

### Filter classes

#### Filter groups

- ISO ePM10 to ISO 16890
- ISO ePM1 to ISO 16890

#### Filter classes

- ePM10 60%
- ePM10 75%
- ePM1 60%
- ePM1 75%
- ePM1 90%

### Construction

- PLA: Frame made of plastic
- GAL: Frame made of galvanised steel

### Useful additions

- Filter wall (SIF)
- Universal casing (UCA)

### Construction features

- Wedge-shaped filter pockets
- Frame depth of construction PLA: 25 mm
- Frame depth of construction GAL: 20, 25 mm
- Number of pockets: 3, 4, 5, 6, 7, 8

#### Materials and surfaces

- Filter media made of non-woven glass fibres
- Frame made of plastic or galvanised sheet steel

#### Standards and guidelines

- Test according to ISO 16890; international standard for general room air distribution; classification of arrestance efficiency based on the measured fractional arrestance efficiency, which is processed into a reporting system for the fine dust arrestance efficiency (ePM)
- For fine dust filters, the fractional arrestance efficiency of a certain size range is determined by aerosols (DEHS and KCl)
- The filters are classified into filter groups ISO ePM10 and ISO ePM1 depending on the tested values
- Construction PLA meets the hygiene requirements of VDI 6022, VDI 3803, DIN 1946 Part 4, ÖNORM H 6021 and ÖNORM H 6020, SWKI VA 104-01 and SWKI 99-3, and EN 16798
- Certificate of conformity for correct use in areas with a potentially explosive atmosphere in accordance with guideline 2014/34/EU and compliance with basic health and safety requirements in accordance with EN 80079-36:2016 and EN 80079-37:2016

## TECHNICAL INFORMATION

<b>Fractional efficiency ePM10 [%] to ISO 16890</b>	60	75	-	-	-
<b>Fractional efficiency ePM1 [%] to ISO 16890</b>	-	-	60	75	90
<b>Initial pressure difference [Pa] at nominal flow rate</b>	55	70	80	100	140
<b>Recommended final pressure difference [Pa]</b>	250 - 350	250 - 350	250 - 350	250 - 350	250 - 350
<b>maximum operating temperature [°C] for plastic frames</b>	60	60	60	60	60
<b>maximum operating temperature [°C] for frame made of galvanised sheet steel</b>	90	90	90	90	90

#### Changing the filter/Final differential pressure

The aim is to find the optimum of the longest possible service life with energetically low differential pressure and safe hygiene. A fixed, recommended value for the final differential pressure can tempt people to insist on keeping to this value, irrespective of its usefulness and today's standards with regard to, for example, energy saving, sustainability or resource conservation. To save costs and energy, we generally recommend the use of technically high-quality filters with low initial differential pressure and a flat differential pressure curve. In addition, the preferred criterion for a filter change should be the differential pressure. For further information, please refer to the installation and maintenance instructions.

#### Specification text

Pocket filters PFG made of non-woven glass fibres as prefilters or final filters for the separation of fine dust in ventilation systems. Filter pockets provide a high dust holding capacity at a low initial differential pressure. Pocket filters made of non-woven glass fibres are available in standard and special sizes; variable number of pockets and pocket depth; filter groups ISO ePM10 and ISO ePM1 according to ISO 16890. Pocket filters made of non-woven glass fibres are Eurovent-certified and compliant with VDI 6022 in terms of hygiene. The pocket filters with optional EX protection PFG-EX may be used in areas with potentially explosive atmospheres of zones 1 and 2 as well as zones 21 and 22 (EX II 2G Ex h IIC Gb and EX II 2D Ex h IIIB Db). The filters must be connected to the ground potential. All conductive and dissipative parts must be connected together and grounded. Conductive dusts are excluded from the application. Under no circumstances should metallic foreign materials enter the filter. Ambient temperature range:  $-40\text{ °C} \leq T_a \leq +80\text{ °C}$ .

#### Materials and surfaces

- Filter media made of non-woven glass fibres
- Frame made of plastic or galvanised sheet steel

#### Construction

- PLA: Frame made of plastic
- GAL: Frame made of galvanised steel

#### Sizing data

- Filter group [ISO 16890]
- Efficiency [%]
- Volume flow rate [ $\text{m}^3/\text{h}$ ]
- Initial differential pressure [Pa]
- Nominal size [mm]

#### Life cycle assessment

A life cycle assessment is available for the product series in form of an Environmental Product Declaration (EPD) that has been checked and published by a programme holder.

PFG	-	ePM1	-	90 %	-	PLA	-	25	/	592 × 592 × 600	×	8
1		2		3		4		5		6		7

1 Type  
PFG Pocket filters made of non-woven glass fibres

2 Classification  
ePM1 Fractional efficiency ePM1 acc. to ISO 16890  
ePM10 Fractional efficiency ePM10 acc. to ISO 16890

3 Separation efficiency  
Separation efficiency [%] according to ISO 16890

4 Construction  
PLA Plastic frame  
GAL Frame made of galvanised sheet steel  
EX Frame made of galvanised sheet steel, for zones 1 and 2 as well as 21 and 22 in areas with potentially explosive atmospheres (EX)

5 Frame depth [mm]  
20 (construction GAL only)  
25

6 Nominal size [mm]  
Specify width × height × depth

7 Number of pockets  
3, 4, 5, 6, 7, 8